

## Between Series Adaptor 33\_BNC-QLA-01-1/1--\_N

### Description

Adaptor plug/jack  
BNC plug (male) / QLA-01 jack (female)

Interface standards  
Series BNC - IEC 61169-8\_MIL-STD-348A/301\_CECC 22120  
Series QLA-01 - NIM-CAMAC-Standard CD/N549



### Technical Data

#### Electrical Data

Impedance other  $\Omega$   
Interface frequency max. 1.4 GHz

#### Mechanical Data

Number of matings 500  
Weight 0.0125 kg

#### Environmental Data

Operating temperature -55 °C to 155 °C  
2011/65/EU (RoHS) compliant

#### Material Data

Interface - BNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	Nickel Plating
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - QLA-01 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Bronze	Gold Plating (Nickel underplated)
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	

### Related Documents

Catalogue drawing DCA-00014383

### Ordering Information

Single package 33\_BNC-QLA-01-1/1--\_NE