




Info@SRICconnectorGage.com
Tel 800.881.9689 • Fax 321.259.9681

[Home](#) [Products](#) [What's New](#) [Info Request](#) [Reps](#) [About Us](#) [Affiliates](#) [Support](#) [Log In](#)

PRODUCTS | [ALL PRODUCTS](#) | [41-941-2050-00](#)



41-941-2050-00



TNC 18GHz jack to TNC 18GHz jack adapter bulkhead mount "O" ring sealed

Quantity : [Add To RFQ](#)



if you do not find it on the site or in the catalog, we will execute virtually any coax design related to our product line and deliver it quickly-usually less than 8 weeks!

Connect From: TNC Female
Connect To: TNC Female
Category: TNC
Gender: Jack-to-Jack
Mounting Style: Bulkhead Mount
Body Material: SST, corrosion-resistant, Non-Magnetic 303, per ASTM A484 & A582
Center Conductor Material: Beryllium Copper per ASTM-B-196, QQ-C-530
Dielectric Material: PTFE Fluorocarbon per ASTM-D-1710
Finish: Center Contacts and solder components shall be plated per MIL-G-45204 Type II, Class I over Nickel plate per QQ-N-290. Body & Body components shall be passivated per ASTM A380
Geometry: Straight
Contact Torque: 4.0 inch-ounces min.
Normal Impedance: 50 Ohm
Frequency Range: DC – 18 GHz
VSWR: 1.15:1 to 18 GHz
Hermetically Sealed?: No
Temperature Rating: -55°C to +100°C
Durability: 500 cycles min.
Corrosion (salt spray): MIL-STD-202, method 101, test condition B 5% salt solution
Vibration High Frequency: MIL-STD-202, method 204, test condition D (20 G's)

[Back](#)



3950 Dow Road Melbourne, FL 32934-9289 ■ info@sriconnectorgage.com ■ Tel 800.881.9689 ■ Fax 321.259.9681



[1.85 mm](#) | [2.4 mm](#) | [2.9 mm](#) | [Adapters](#) | [Cable Connectors](#) | [Receptacles](#) | [ZMA](#)
[Home](#) | [Products](#) | [What's New](#) | [Info Request](#) | [Reps](#) | [About Us](#) | [Privacy](#) | [Affiliates](#) | [Support](#) | [Log In](#)