

Between Series Adaptor 32_N-SMC-50-1/1--_N

Description

Adaptor plug/plug
N plug (male) / SMC plug (male)



Interface standards
Series N - IEC 61169-16_MIL-STD-348A/304_CECC 22210
Series SMC - IEC 60169-9_MIL-STD-348A/312_CECC 22140

Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	10 GHz		
Frequency range	DC to 2 GHz	2 to 4 GHz	4 to 10 GHz
Return loss	≥ 26 dB	≥ 20 dB	≥ 15 dB

Mechanical Data

Number of matings	500
Weight	0.0264 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - N plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - SMC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	Gold Plating (Nickel underplated)

Related Documents

Catalogue drawing	DCA-00014482
-------------------	--------------

Ordering Information

Single package	32_N-SMC-50-1/1--_NE
----------------	----------------------