

DESCRIPTION

PMI MODEL: APD-2-DC10G-SFF IS A 2 WAY POWER DIVIDER/COMBINER OPERATING OVER THE DC TO 10.0 GHz FREQUENCY RANGE. THIS COMPACT PACKAGE OFFERS 10 dB TYPICAL ISOLATION WHILE MAINTAINING A TYPICAL INSERTION LOSS OF 3.3 dB, AND A MAXIMUM AMPLITUDE BALANCE OF ± 1.0 dB MAXIMUM.

SPECIFICATIONS

- FREQUENCY RANGE: ----- DC TO 10.0 GHz
- INSERTION LOSS: ----- 3.3 dB TYPICAL
4.0 dB MAXIMUM
- ISOLATION: ----- 10 dB TYPICAL
- AMPLITUDE BALANCE: ----- ± 1.0 dB MAXIMUM
- CONNECTORS: ----- SMA FEMALE
- SIZE: ----- 26.92 mm x 21.59 mm x 12.70 mm
1.06" x 0.85" x 0.50"
- FINISH: ----- BLUE EPOXY POLIMIDE COATING
IAW MIL-C-22750, TYPE I OVER
EPOXY POLIMIDE PRIMER IAW
MIL-P-23377, TYPE I, CLASS 1 OR 3.

ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -55 °C TO +85 °C (OPERATING)
-65 °C TO +125 °C (STORAGE)
- HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202, METHOD 213B COND. B
- VIBRATION: ----- MIL-STD-202, METHOD 204D COND. B
- ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE


NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

ALL DIMENSIONS
ARE IN mm [INCH]
TOLERANCES:
X.XX ± 0.508 [0.020]
X.XXX ± 0.254 [0.010]

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	1/25/17	

MECHANICAL OUTLINE



PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE		
DRAWN		1/25/17		PRODUCT FEATURE APD-2-DC10G-SFF		
CHECKED				SIZE	FSCM NO.	DWG NO.
ISSUED				A	05XQ0	PRELIMINARY
				SCALE	N:S	SHEET 1 OF 1