
JYEBAO www.jyebao.com.tw

ADS-AQ3A8	**Snap on SMA Plug To SMA Jack**	**50Ω**



Note: (1)Snap on SMA plug with locking mechanism
(2) Snap on SMA plug is specified up to 20000 matings minimum
(3) To get a proper mating one should first snap on the SMA plug and then give it a little turn.

Typical VSWR

Part Number	1Ghz	2Ghz	3Ghz	4Ghz	5Ghz	6Ghz	7Ghz	8Ghz	9Ghz
ADS-AQ3A8	1.04	1.04	1.04	1.05	1.05	1.05	1.05	1.05	1.07
	10Ghz	11Ghz	12Ghz	13Ghz	14Ghz	15Ghz	16Ghz	17Ghz	18Ghz
	1.07	1.09	1.09	1.09	1.09	1.09	1.2	1.31	1.34

Parts	Material	Plating (Micro-inch)
Insulator	Teflon	
Spring	Stainless	
Contact Pin	Stainless	Gold 10 Over Nickel 50 Over Copper 50
Contact Body	Stainless	Passivated
Coupling Nut	Stainless	Passivated

Weight: 5.64 g

This part number complies with RoHS.
Notice: JYEBAO reserves the right to make modifications deemed appropriate.