Data Sheet

Between Series Adaptor
33_QLA-BNC-01-1/1--_N

Description

Adaptor plug/jack
QLA-01 plug (male) / BNC jack (female)



Interface standards
Series QLA-01 - NIM-CAMAC-Standard CD/N549
Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Impedance	other Ω
Interface frequency max.	1.4 GHz

Mechanical Data

Number of matings	500
Weight	0.0085 kg

Environmental Data

Operating temperature	-55 °C to 150 °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - QLA-01 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	Nickel Plating
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	

Interface - BNC jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing	DCA-00014252

Ordering Information

Single package	33_QLA-BNC-01-1/1--_NE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000195259 M / PDO C / date of publication: 23.03.2016 13:43:14 / uncontrolled copy