


DESCRIPTION:

PMI MODEL NUMBER APD-32-2R5G2R9G-SMF IS A 2.5 TO 2.9 GHz, 32-WAY POWER DIVIDER. THIS POWER DIVIDER DEMONSTRATES LOW 2.0 dB INSERTION LOSS AS WELL AS 20 dB MINIMUM OF ISOLATION.

SPECIFICATIONS:

- FREQUENCY: 2.5 to 2.9 GHz
- INSERTION LOSS: 2.0 dB max.
- ISOLATION: 20 dB min.
- VSWR: Input: 1.6:1 max.
Output: 1.4:1 max.
- AMPLITUDE BALANCE: ± 0.8 dB max.
- PHASE BALANCE: $\pm 7^\circ$ max.
- POWER HANDLING: Forward: 30 Watts max.
Reverse: 1 Watt max.
(@ 1.2 VSWR LOAD)
- IMPEDENCE: 50 ohms
- CONNECTORS: Input: SMA (M)
Output: SMA (F)
- FINISH: PAINTED BLUE



PMI CONFIDENTIAL AND PROPRIETARY

ENVIRONMENTAL RATINGS:

- TEMPERATURE: -40°C TO +85°C (OPERATING)
- HUMIDITY: UP TO 95%, NON-CONDENSING

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ± 0.020
X.XXX ± 0.010

APPROVALS		DATE		TITLE			
DRAWN		1/16/17		PRODUCT FEATURE			
CHECKED				APD-32-2R5G2R9G-SMF			
ISSUED							
SIZE		FSCM NO.		DWG NO.		REV.	
A		05XQ0		PRELIMINARY		-	
SCALE		N:S				SHEET	
						1 OF 1	