Data Sheet

Between Series Adaptor
33_PC7-PC35-50-1/1--_U

Description



Adaptor plug/jack
PC 7 plug (male) / PC 3.5 jack (female)

For Test & Measurement applications
Precision adaptor

Interface standards
Series PC 7 - IEEE STD 287_ANSI C 16.43
Series PC 3.5 - IEC 60169-23

Technical Data

Electrical Data

Impedance	50 Ω	
Interface frequency max.	18 GHz	
Frequency range	DC to 15 GHz	15 to 18 GHz
Return loss	≥ 32 dB	≥ 27 dB
Electrical length	35.97 mm	

Mechanical Data

Number of matings	500
Weight	0.0476 kg

Environmental Data

Operating temperature	-55 °C to 70 °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - PC 7 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - PC 3.5 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	

Ordering Information

Single package	33_PC7-PC35-50-1/1--_UE

Remarks

Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.