

DESCRIPTION

PMI MODEL APD-3-800M2D5G-NFF-50W IS A THREE WAY POWER DIVIDER FEATURING HIGH ISOLATION, LOW INSERTION LOSS, AND LOW VSWR. IT IS DESIGNED FOR BROADBAND USE AND HIGH RELIABILITY.

SPECIFICATIONS

- FREQUENCY RANGE: 0.8 TO 2.5 GHz
- INSERTION LOSS: ≤ 0.6 dB
- VSWR: $\leq 1.30:1$
- ISOLATION: 20 dB MINIMUM
- AMPLITUDE BALANCE: $\leq \pm 0.35$ dB
- PHASE BALANCE: $\leq \pm 3^\circ$
- POWER HANDLING: FORWARD ≤ 50 W
REVERSED ≤ 1 W
- IMPEDANCE: 50 Ω
- CONNECTORS: N-FEMALE (X4)
- FINISH: PAINTED BLUE

ENVIRONMENTAL RATINGS

- TEMPERATURE: -55 °C TO +85 °C (OPERATING)
-65 °C TO +125 °C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION


ALL DIMENSIONS ARE IN INCHES

TOLERANCES:
X.XX ± 0.020
X.XXX ± 0.010

PMI CONFIDENTIAL AND PROPRIETARY

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	05/14/15	

MECHANICAL OUTLINE



PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE			
DRAWN <i>M. Berry</i>		05/14/15		PRODUCT FEATURE APD-3-800M2D5G-NFF-50W			
CHECKED				SIZE	FSCM NO.	DWG NO.	REV.
ISSUED				A	05XQ0	27025641	A1
SCALE		N:S		SHEET		1 OF 1	