Data Sheet

Between Series Adaptor
33_BNC-MMCX-50-1/1--_U

Description

Adaptor plug/jack
BNC plug (male) / MMCX jack (female)



Interface standards
Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120
Series MMCX - SUHNER-MMCX

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
VSWR	DC - 4 GHz ≤ 1.05 + 0.025 f (GHz)

Mechanical Data

Number of matings	500
Weight	0.0111 kg

Environmental Data

Operating temperature	°C to °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - BNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - MMCX jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing	DCA-00014387

Ordering Information

Single package	33_BNC-MMCX-50-1/1--_UE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000195397 R / PDO D / date of publication: 12/4/2014 4:36:10 PM / uncontrolled copy