
THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES,
ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED
WITHOUT WRITTEN PERMISSION FROM RF INDUSTRIES.
ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.

ALL DIMENSIONS ARE REFERENCE ONLY

PART NO. **RHV-134**

REV	DESCRIPTION	DWN	DATE	APPROVED
–	ENGINEERING RELEASE	CZS	8/22/96	JDMc



SPECIFICATIONS:

IMPEDANCE: Non–Constant
WORKING VOLTAGE: 5K V rms @ sea level
TEMPERATURE RANGE: –65°C TO 165°C
INSULATION RESISTANCE: 5k M Ohms min.

#	DESCRIPTION	QTY	MATERIAL	FINISH
1	BODY	1	BRASS	NICKEL, 100µ"
2	INSULATOR	2	PTFE	---
3	CONTACT	1	BRASS	GOLD, 30µ"
4	SLEEVE	1	BRASS	NICKEL, 100µ"
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				

007777

APPROVALS	DATE
DRAWN C. ZUNIGA	11/7/01
CHECKED	11-7-01
ORJ DRAWN C. ZUNIGA	11/7/01

UNLESS OTHERWISE SPECIFIED:
1. REMOVE ALL BURRS
2. BREAK ALL CORNERS & EDGES .005 R. MAX.
3. CHAMFER 1ST & LAST THREADS 45°
4. SURFACE ROUGHNESS 63 FINISH MIL–STD–10
5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN .002 T.I.R.
6. ALL DIMENSIONS ARE AFTER PLATING.

DIMENSIONS ARE IN INCHES AND [MILLIMETERS]
UNLESS OTHERWISE NOTED TOLERANCES ARE:

DECIMALS	DIAMETER
.XXX±.003 [.08]	.XXX±.001 [.03]
.XX±.005 [.13]	.XX±.003 [.08]

RF connectors
DIVISION OF RF INDUSTRIES, LTD.
7610 MIRAMAR RD
SAN DIEGO,CA 92126
(858) 549–6340
(858) 549–6345 FAX

MHV JACK TO JACK

ADAPTER

SIZE	CABLE GROUP	DWG NO.	REV
A	N/A	RHV–134	–

SCALE: NTS	CAD FILE OUTLINE	SHEET 1 OF 1