

REVISIONS				DATE	APPROVED
200	REV	DESCRIPTION		2/7/00	
-		ORIGINAL RELEASE			

Description:

Low Noise Amplifier designed for Military and Industrial applications. This amplifier is supplied in our standard PE2 housing that can be used as a SMA connectorized or a surface mount component. Other packages and connector types are available.

This model provides the following performance. Data is available upon request.

Specifications:

Frequency Range: 0.5 to 8.0 GHz
Gain: 30dB Typ.
Gain Flatness: +/-1.0dB Max.
Noise Figure: 4.5dB Typ.
OP1dB: 13dBm Min.
VSWR Input/Output: 2.0:1 Max.
DC Voltage Supply: +12 to +15VDC
DC Current Draw: 130mA Max.

Features:

Internal Voltage Regulation
Unconditional Stability
Standard Operating Temperature -20 to +70 Deg. C

Available Options:

Various Package types
Various Connector types
Temperature Compensation
Hermetic Sealing
Gain and Phase Matching
MIL-STD-883 Screening Available

Environmental Ratings:

Temperature: -20 to +70 Deg. C (Operating) ; -55 to +85 Deg C (Available)

Humidity: -55 to +125 Deg. C (Storage)


Shock: MIL-STD-202F, METHOD 103B COND B.

Altitude: MIL-STD-202F, METHOD 213B COND B.


Temperature Cycle: MIL-STD-202F, METHOD 105C COND B.

Note: The above specifications are subject to change or revision.

PE2 HOUSING WITH CARRIER



PE2 HOUSING WITHOUT CARRIER (SURFACE MOUNT)



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:		ANGLES		FINISH:		DO NOT SCALE DRAWING	
FRACTIONS	DECIMALS	±	±	±	±	±	±
.XXX	± 0.005						
MATERIAL:		6061-T6 Aluminum		K. Mason		DATE	
6061-T6 Aluminum		K. Mason		2/27/00		DATE	
Gold Plate over Nickel		N/A		N/A		N/A	
5715 Industry Lane, Unit 11		FREDERICK, MARYLAND		PRODUCT FEATURE		PE2-30-0P5880-4P5-15-12-SFF	
B. 1LK53		WEB - MODEL		A		1 OF 1	