Data Sheet

Between Series Adaptor
33_PC35-MCX-50-1/111_N

Description



Adaptor plug/jack
PC 3.5 plug (male) / MCX jack (female)

For Test & Measurement applications
Precision adaptor

Interface standards
Series PC 3.5 - IEC 60169-23
Series MCX - IEC 60169-36_CECC 22220

Technical Data

Electrical Data

Impedance	50 Ω	
Interface frequency max.	6 GHz	
Frequency range	DC to 3.5 GHz	3.5 to 6 GHz
Return loss	≥ 30 dB	≥ 26 dB

Mechanical Data

Number of matings	500
Weight	0.0068 kg

Environmental Data

Operating temperature	-65 °C to 90 °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - PC 3.5 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Copper Beryllium Alloy	SUCOPRO Plating
Body	Copper Beryllium Alloy	SUCOPRO Plating
Insulator	PFA / PTFE	
Coupling nut	Bronze	Gold Plating (Nickel underplated)

Interface - MCX jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Copper Beryllium Alloy	SUCOPRO Plating
Body	Copper Beryllium Alloy	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing	DCA-00014288

Ordering Information

Single package	33_PC35-MCX-50-1/111_NE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000195294 P / PDO D / date of publication: 12/4/2014 4:36:25 PM / uncontrolled copy