
Data Sheet

Between Series Adaptor
33_SMA-MBX-50-1/11-_N

Description

Adaptor plug/jack
SMA plug (male) / MBX jack (female)



Interface standards
Series SMA - IEC 60169-15_MIL-STD-348A/310_CECC 22110
Series MBX - HUBER+SUHNER MBX

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz
Frequency range	DC to 6 GHz
Return loss	≥ 28 dB

Mechanical Data

Number of matings	500
Weight	0.005181 kg

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - SMA plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Body	Bronze	SUCOPRO Plating
Insulator	PFA / PTFE	
Coupling nut	Stainless Steel	

Interface - MBX jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Body	Bronze	SUCOPRO Plating
Insulator	PTFE / LCP	

Related Documents

Outline drawing	DOU-00146087

Ordering Information

Single package	33_SMA-MBX-50-1/11-_NE

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000335117 H / PDO C / date of publication: 12/4/2014 4:40:08 PM / uncontrolled copy