

## Within Series Adaptor 32\_MMBX-50-0-14/111\_N

### Description

Adaptor plug/plug  
MMBX plug (male) / MMBX plug (male)

Slide - snap interface

Interface standard  
Series MMBX - SUHNER-MMBX



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 12.4 GHz

#### Mechanical Data

Number of matings 100  
Weight 0.0019 kg

#### Environmental Data

Operating temperature -55 °C to 155 °C  
2011/65/EU (RoHS) compliant

#### Material Data

Interface - MMBX plug (male)

| Piece Parts    | Material                       | Surface Plating |
|----------------|--------------------------------|-----------------|
| Centre contact | Copper Beryllium Alloy         | SUCOPRO Plating |
| Outer contact  | Bronze                         | SUCOPRO Plating |
| Body           | Bronze                         | SUCOPRO Plating |
| Insulator      | PTFE (Polytetrafluoroethylene) |                 |

Interface - MMBX plug (male)

| Piece Parts    | Material                       | Surface Plating |
|----------------|--------------------------------|-----------------|
| Centre contact | Copper Beryllium Alloy         | SUCOPRO Plating |
| Outer contact  | Bronze                         | SUCOPRO Plating |
| Body           | Bronze                         | SUCOPRO Plating |
| Insulator      | PTFE (Polytetrafluoroethylene) |                 |

### Related Documents

Outline drawing DOU-00064614

### Ordering Information

Tray package 32\_MMBX-50-0-14/111\_NY