

Between Series Adaptor 31_4195-716-50-1/133_W

Description

PIM Adaptor jack/jack
4.1/9.5 jack (female) / 7/16 jack (female)

Interface standards
Series 4.1/9.5 - IEC 60169-11_DIN 47231_VG 95277
Series 7/16 - IEC 61169-4_CECC 22190_DIN 47223_VG 95250

Benefits

Low passive intermodulation (PIM) adaptor
For Test & Measurement applications



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz
PIM, 3rd order intermodulation distortion (IMD) max.	Static -165 dBc at 2x 43 dBm / 20 W carrier

Mechanical Data

Number of matings	500
Weight	0.0981 kg

Environmental Data

Operating temperature	-45 °C to 85 °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - 4.1/9.5 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Interface - 7/16 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00014624
-----------------	--------------

Ordering Information

Single package	31_4195-716-50-1/133_WE
----------------	-------------------------