

Between Series Adaptor 33_BNC-MMCX-50-1/1--_N

Description

Adaptor plug/jack
BNC plug (male) / MMCX jack (female)

Interface standards
Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120
Series MMCX - SUHNER-MMCX



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 4 GHz
VSWR DC - 4 GHz
 $\leq 1.03 + 0.05 f \text{ (GHz)}$

Mechanical Data

Number of matings 500
Weight 0.0114 kg

Environmental Data

Operating temperature -55 °C to 155 °C
2011/65/EU (RoHS) compliant

Material Data

Interface - BNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - MMCX jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing DCA-00014387

Ordering Information

Single package 33_BNC-MMCX-50-1/1--_NE