

Between Series Adaptor 33_BNC-N-Q50-4/133_N

Description

Adaptor plug/jack

BNC Quick-mate plug (male) / N jack (female)

Quick-mate coupling mechanism, pluggable without tightening

For Test & Measurement applications

Interface standards

Series BNC Quick-mate - HUBER+SUHNER Quick-mate

Series N - IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
Frequency range	DC to 4 GHz
Return loss	≥ 29 dB

Mechanical Data

Number of matings	500
Weight	0.0417 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS)	compliant

Material Data

Interface - BNC Quick-mate plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Interface - N jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00014391
-----------------	--------------

Ordering Information

Single package	33_BNC-N-Q50-4/133_NE
----------------	-----------------------

Remarks

Durability of QUICK MATE interface: 1000 matings