

Between Series Adaptor 33_QMA-PC35-50-1/1--_N

Description

Adaptor plug/jack
QMA plug (male) / PC 3.5 jack (female)

QuickLock Interface
For Test & Measurement applications

Interface standards
Series QMA - QMA QLF compliant
Series PC 3.5 - IEC 60169-23



Technical Data

Electrical Data

| | | | |
|--------------------------|---------------|--------------|-------------|
| Impedance | 50 Ω | | |
| Interface frequency max. | 18 GHz | | |
| Frequency range | DC to 1.5 GHz | 1.5 to 6 GHz | 6 to 18 GHz |
| Return loss | ≥ 35 dB | ≥ 30 dB | ≥ 20 dB |
| Electrical length | 25.5 mm | | |

Mechanical Data

| | |
|-------------------|-----------|
| Number of matings | 500 |
| Weight | 0.0122 kg |

Environmental Data

| | |
|--|-------------------------------|
| Operating temperature 2011/65/EU (RoHS) | -60 °C to 100 °C compliant |
|--|-------------------------------|

Material Data

Interface - QMA plug (male)

| Piece Parts | Material | Surface Plating |
|----------------|----------------------------|-----------------|
| Centre contact | Copper Beryllium Alloy | SUCOPRO Plating |
| Outer contact | Copper Beryllium Alloy | SUCOPRO Plating |
| Body | Stainless Steel | |
| Insulator | Air Dielectric - Bead - PS | |

Interface - PC 3.5 jack (female)

| Piece Parts | Material | Surface Plating |
|----------------|----------------------------|-----------------|
| Centre contact | Copper Beryllium Alloy | SUCOPRO Plating |
| Outer contact | Stainless Steel | |
| Body | Stainless Steel | |
| Insulator | Air Dielectric - Bead - PS | |

Related Documents

| | |
|-----------------|--------------|
| Outline drawing | DOU-00014031 |
|-----------------|--------------|

Ordering Information

| | |
|----------------|-------------------------|
| Single package | 33_QMA-PC35-50-1/1--_NE |
|----------------|-------------------------|