

## Between Series Adaptor 32\_QN-716-50-1/113\_W

### Description

PIM Adaptor plug/plug  
QN plug (male) / 7/16 plug (male)

Interface standards  
Series QN - QN QLF compliant  
Series 7/16 - IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250

#### Benefits

Low passive intermodulation (PIM) adaptor  
For Test & Measurement applications



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	7.5 GHz
PIM, 3rd order intermodulation distortion (IMD) max.	Static -155 dBc at 2x 43 dBm / 20 W carrier

#### Mechanical Data

Number of matings	500
Weight	0.0873 kg

#### Environmental Data

Operating temperature 2011/65/EU (RoHS)	-40 °C to 125 °C compliant
--------------------------------------------	-------------------------------

#### Material Data

Interface - QN plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	

Interface - 7/16 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00013951
-----------------	--------------

### Ordering Information

Single package	32_QN-716-50-1/113_WE
----------------	-----------------------

### Remarks

3rd order passive intermodulation max.: static -165 dBc typ.

## Between Series Adaptor 32\_QN-716-50-1/113\_W