

Description:

PMI Model Number: PBB-15-220-12-LCA Assembly Drawing is a 2 to 20 GHz low noise amplifier. This amplifier is supplied in our standard PE2 housing that can be used as a SMA connectorized or a surface mount component.

Specifications:

Frequency Range:	2 to 20 GHz
Gain:	+15dB Typ
Gain Flatness:	±1.75dB Typ
Noise Figure:	3.0dB Typ
OP1dB:	+12dBm Typ
VSWR Input/Output:	2.0:1 Max
DC Supply:	+12VDC @ 75mA Typ
Connectors In/Out:	SMA Female
Finish:	Gold Plated

Features:

Internal Voltage Regulation
Unconditional Stability

Available Options:

Various Package types
Various Connector types
Temperature Compensation
Gain and Phase Matching
MIL-STD-883 Screening Available

Environmental Ratings:


Temperature:	-54°C to + 95°C (Operating) -65°C to +125°C (Storage)
Humidity:	MIL-STD-202F, METHOD 103B COND B.
Shock:	MIL-STD-202F, METHOD 213B COND B.
Altitude:	MIL-STD-202F, METHOD 105C COND B.
Temperature Cycle:	MIL-STD-202F, METHOD 107D COND A

Note: The above specifications are subject to change or revision.


ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.010
X.XXX ±0.005

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	ORIGINAL RELEASE	2/8/13	

PE2 HOUSING WITH CARRIER



PE2 HOUSING WITHOUT CARRIER (SURFACE MOUNT)



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001:2000 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN	afk	2/8/13		PRODUCT FEATURE PBB-15-220-12-LCA	
CHECKED				SIZE	FSCM NO.
ISSUED				A	05XQ0
				DWG NO.	LCA MODEL
				SCALE	N:S
				SHEET	1 OF 1