Data Sheet

Coaxial Cable Connector
11_BNC-50-1-1/133_N

Description

Straight cable plug

Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz

Mechanical Data

Centre contact	soldered
Outer contact	clamped
Weight	0.0175 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00071073
Catalogue drawing	DOU-00007659
Assembly instruction	DOC-0000179064

Ordering Information

Single package	11_BNC-50-1-1/133_NE

Additional Information

Suitable cables	RG_178_B/U, RG_196_A/U

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000182470 T / PDO D / date of publication: 10.05.2017 17:34:45 / uncontrolled copy