Data Sheet

Coaxial Cable Connector
24_BNC-50-7-3/133_N

Description

Straight bulkhead cable feed through

Interface standards
IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0221 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00009720
Catalogue drawing	DCA-00009722
Assembly instruction	DOC-0000186538
Mounting hole	DOU-00008751

Ordering Information

Single package	24_BNC-50-7-3/133_NE

Additional Information

Suitable cables	RG_213_/U, GX_07272, G_07262, RADOX_RF_213

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.