Data Sheet

Coaxial Cable Connector
24_BNC-75-3-5/133_N

Description

Straight bulkhead cable feed through

Interface standards
Interface compatible with IEC 61169-8



Technical Data

Electrical Data

Impedance	75 Ω
Interface frequency max.	1 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0161 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Crimp ferrule	Copper Beryllium Alloy	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00071735
Catalogue drawing	DCA-00008942
Assembly instruction	DOC-0000179061
Mounting hole	DOU-00008751

Ordering Information

Single package	24_BNC-75-3-5/133_NE

Additional Information

Suitable cables	G_03233_D

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000185413 K / PDO D / date of publication: 10.05.2017 14:22:24 / uncontrolled copy