# Data Sheet

## Coaxial Panel Connector
## 22_BNC-75-0-4/133_N

## Description

Straight bulkhead receptacle jack

Interface standards
Interface compatible with IEC 61169-8



## Technical Data

### Electrical Data

| | |
|---|---|
| Impedance | 75 Ω |
| Interface frequency max. | 1 GHz |

### Mechanical Data

| | |
|---|---|
| Number of matings | 500 |
| Weight | 0.0072 kg |

### Environmental Data

| | |
|---|---|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS) | compliant |

### Material Data

| Piece Parts | Material | Surface Plating |
|---|---|---|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |
| Fastening nut | Brass | SUCOPLATE (R) Plating |
| Washer | Bronze | SUCOPLATE (R) Plating |

## Related Documents

| | |
|---|---|
| Outline drawing | DOU-00071690 |
| Catalogue drawing | DCA-00010480 |
| Mounting hole | DOU-00008762 |

## Ordering Information

| | |
|---|---|
| Single package | 22_BNC-75-0-4/133_NE |



Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.