Data Sheet

Coaxial Cable Connector
11_BNC-75-5-6/133_N

Description

Straight cable plug



Interface standards
Interface compatible with IEC 61169-8

Technical Data

Electrical Data

Impedance	75 Ω
Interface frequency max.	1 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0114 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Catalogue drawing	DCA-00006630
Assembly instruction	DOC-0000179061

Ordering Information

Single package	11_BNC-75-5-6/133_NE

Additional Information

Suitable cables	G_05133_D, Belden 8281

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000183828 R / PDO F / date of publication: 10.05.2017 15:30:03 / uncontrolled copy