DESCRIPTION

PMI MODEL: A-4D-2G20G-28G-2R6N-10P is an ultra-wide bandwidth 50-ohm matched distributed amplifier in a compact housing with 4 mounting holes to improve contact for heat transfer between chassis and heatsink.

Features:
- Unconditionally stable under all terminations, open to short
- Unconditionally stable over temperature
- Integrated input/output blocking capacitors
- Single positive power supply
- Internal DC regulated voltage
- Internal reverse polarity protection
- Field replaceable SMA connectors

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	—	PRELIMINARY	7/18/2016	HAI SAY

MECHANICAL OUTLINE



SPECIFICATIONS AT +25° C

- FREQUENCY RANGE: ---------- 2.0 GHz TO 20.0 GHz
- GAIN: ---------- 28 dB MIN.
- GAIN FLATNESS: ---------- ±1.5 dB MAX.
- NOISE FIGURE: ---------- 2.6 dB MAX. NOTE: DC COUPLED
- VSWR IN: ---------- 2.2:1 MAX.
- VSWR OUT: ---------- 2.2:1 MAX.
- P1DB OUT: ---------- 10 dBm MIN.
- DC POWER SUPPLY: ---------- +12 TO +15 V @ 150 mA NOM.
- CONNECTORS (IN/OUT): ---------- SMA FEMALE
- FINISH: ---------- GOLD PLATED

ENVIRONMENTAL RATINGS

- TEMPERATURE: ---------- -25 °C TO +75 °C (OPERATING) -65 °C TO +125 °C (STORAGE)

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES (mm)
TOLERANCES (INCHES):
X.XX ±0.010
X.XXX ±0.005

PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.
7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: (301)-662-5019, FAX: (301)-662-1731
WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED

APPROVALS	DATE
DRAWN HAI SAY	07/18/16
CHECKED HAI SAY	07/18/16
ISSUED	

TITLE: PRODUCT FEATURE
AMPLIFIER 2 GHz TO 20 GHz
A-4D-2G20G-28G-2R6N-10P

SIZE	FSCM NO.	DWG NO.	REV.
A	05XQ0	PRELIMINARY	-

SCALE N:S SHEET 1 OF 1