Data Sheet

Coaxial Cable Connector
11_C-50-3-7/133_N

Description

Straight cable plug

Interface standards
IEC 60169-7_MIL-STD-348A/302

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	11 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0281 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO / Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00008120
Catalogue drawing	DCA-00006621
Assembly instruction	DOC-0000179851

Ordering Information

Single package	11_C-50-3-7/133_NE

Additional Information

Suitable cables	RG_58_C/U, G_03232, GX_03272

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.