

DESCRIPTION

PMI MODEL: A-5D-100M18G-35G-2R8N-15P is an ultra-wide bandwidth 50-ohm matched distributed amplifier in a compact housing with 4 mounting holes to improve contact for heat transfer between chassis and heatsink.

Features:

- Unconditionally stable under all terminations, open to short
- Unconditionally stable over temperature
- Integrated input/output blocking capacitors
- Single positive power supply
- Internal DC regulated voltage
- Internal reverse polarity protection
- Field replaceable SMA connectors

SPECIFICATIONS

- FREQUENCY RANGE: ----- 100 MHz TO 18 GHz
- GAIN: ----- 35 dB MIN.
- GAIN FLATNESS: ----- ± 2 dB MAX.
- NOISE FIGURE: ----- 2.8 dB MAX.
- VSWR IN: ----- 2.3:1 MAX.
- VSWR OUT: ----- 2.3:1 MAX.
- P1DB OUT: ----- 15 dBm MIN.
- DC POWER SUPPLY: ----- +15 V @ 250 mA NOM.
- CONNECTORS (IN/OUT): ----- SMA FEMALE
- FINISH: ----- GOLD PLATED

ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -54 °C TO +85 °C (OPERATING)
-65 °C TO +125 °C (STORAGE)



NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

ALL DIMENSIONS
ARE IN INCHES (mm)
TOLERANCES:
X,XX ± 0.020
X,XXX ± 0.010

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	—	PRELIMINARY	6/17/2016	

MECHANICAL OUTLINE



PLANAR MONOLITHICS INDUSTRIES, INC.
7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: (301)-662-5019, FAX: (301)-662-1731
WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE				REV.
DRAWN <i>EJB</i>		06/24/16	PRODUCT FEATURE AMPLIFIER 100 MHz TO 18 GHz A-5D-100M18G-35G-2R8N-15P				-
CHECKED <i>HAJ SBY</i>		06/24/16	SIZE A	FSCM NO. 05XQ0	DWG NO.	PRELIMINARY	
ISSUED			SCALE N:S	SHEET		1 OF 1	