

DESCRIPTION


PMI MODEL: LPF100-140-NFF-50W IS A HIGH POWER, LOW PASS FILTER HAVING A CUT-OFF FREQUENCY OF 100 MHz. THIS FILTER OFFERS LOW INSERTION LOSS OF 1 dB TYPICAL AND OVER 80 dB OF REJECTION @ 140 MHz. THE FILTER IS DESIGNED FOR 50 Ω IMPEDANCE AND CAN HANDLE INPUT POWER LEVELS TO 50 WATTS CW.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	11/16/15	

MECHANICAL OUTLINE

SPECIFICATIONS

- FREQUENCY RANGE: ----- DC TO 100 MHz
- PASSBAND INSERTION LOSS: ----- 1 dB TYPICAL
- REJECTION @ 140 MHz: ----- -80 dB MINIMUM
- IMPEDANCE: ----- 50 Ω
- PASSBAND VSWR: ----- 2.0:1 TYPICAL
- CONNECTORS: ----- N-TYPE FEMALE
- POWER HANDLING: ----- 50 W CW
- SIZE: ----- 2.0" x 6.0" x 1.25"



ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -55 °C TO +85 °C (OPERATING)
-65 °C TO +125 °C (STORAGE)
- HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202, METHOD 213B COND. B
- VIBRATION: ----- MIL-STD-202, METHOD 204D COND. B
- ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS
ARE IN INCHES (mm)
TOLERANCES:
X.XX ± 0.020
X.XXX ± 0.010

PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN <i>M. Berry</i>		11/16/15		PRODUCT FEATURE LPF100-140-NFF-50W	
CHECKED				SIZE A	FSCM NO. 05XQ0
ISSUED				DWG NO.	PRELIMINARY
				SCALE N:S	SHEET 1 OF 1