

DESCRIPTION

PMI MODEL: DD-50M700M-700-SMF IS A LOW NOISE TUNNEL DIODE DETECTOR OPERATING OVER THE 50 MHz TO 700 MHz FREQUENCY RANGE. THIS MODEL OFFERS EXCELLENT TEMPERATURE STABILITY.

SPECIFICATIONS

- FREQUENCY RANGE: ----- 50 TO 700 MHz
- VOLTAGE SENSITIVITY: ----- 700 mV/mW MINIMUM
- OUTPUT POLARITY: ----- NEGATIVE
- INPUT POWER: ----- 50 mW CW MAXIMUM
- IMPEDANCE: ----- 50 OHMS TYPICAL
- CONNECTORS: ----- 2.92 mm MALE IN/ SMA FEMALE OUT AND COMPATIBLE WITH SMA
- SIZE: ----- (L) 1.30" x Ø0.31"
(L) 33.02 mm x Ø7.87 mm
- FINISH: ----- NICKEL

ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -45 °C TO +85 °C (OPERATING)
-55 °C TO +95 °C (STORAGE)
- HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202, METHOD 213B COND. G (50g, 11 ms)
- VIBRATION: ----- MIL-STD-202, METHOD 204D COND. D (20 g, 10 - 2000 MHz)
- ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION


PMI CONFIDENTIAL AND PROPRIETARY

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	12/19/18	

LABEL



MECHANICAL OUTLINE



PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: (301)-662-5019, FAX: (301)-662-1731
WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE		
DRAWN		JPH		12/19/18		
REDRAWN						
ISSUED						
SIZE		A		FSCM NO.		DWG NO.
				05XQ0		PRELIMINARY
SCALE		N:S				SHEET
						1 OF 1