

DESCRIPTION

PMI MODEL TD-30T-SHS-218-2G4G-PECL-OPT4G6G IS A HIGH SPEED, LVPECL LOGIC OUTPUT THRESHOLD DETECTOR DESIGNED TO OPERATE FROM 4.0 GHz TO 6.0 GHz. THIS DETECTOR HAS A PROPAGATION DELAY OF 15 ns MAXIMUM.

SPECIFICATIONS

- FREQUENCY RANGE:..... 4.0 to 6.0 GHz
- VSWR:..... 3.0 : 1 MAXIMUM @ -20 dBm
- MINIMUM SIGNAL LEVEL
FOR LOGIC 1:..... -20 dBm @ 2 GHz
- THRESHOLD VARIATION
OVER FREQUENCY
(ANY 1 GHz WINDOW):..... ± 0.5 dB
- MINIMUM SIGNAL LEVEL
FOR LOGIC 0:..... -25 dBm
- DYNAMIC RANGE:..... UP TO +10 dBm
- PROPAGATION DELAY 15 ns MAX
(FROM 50% OF AN INPUT
OF -20 dBm):
- OUTPUT LOGIC:..... LVPECL COMPATIBLE
- PROPAGATION DELAY 15 ns MAX
(FROM 50% OF AN INPUT
OF +10 dBm):
- DC POWER SUPPLY
+V:..... +15 VOLTS @ 100 mA MAX
-V:..... -15 VOLTS @ 100 mA MAX
- SIZE:..... 2.2" x 1.50" x 0.40"
- WEIGHT:..... ≤ 3 OUNCES
- FINISH:..... GOLD PLATED


ENVIRONMENTAL RATINGS

- TEMPERATURE:**..... -55°C TO +85°C (OPERATING)
-65°C TO +100°C (STORAGE)
- HUMIDITY:**..... MIL-STD-202F, METHOD 103B COND. B
- SHOCK:**..... MIL-STD-202F, METHOD 213B COND. B
- VIBRATION:**..... MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE:**..... MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE:**..... MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

NOTES:
1) DIMENSIONS ARE IN INCHES
2) TOLERANCES: X.XX ± 0.020
X.XXX ± 0.010
3) WEIGHT: 2.75 OZ

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	4/6/18	



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-4700 FAX: 301-662-4938
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN		10/4/13		PRODUCT FEATURE	
REDRAWN		4/6/18		TD-30T-SHS-218-2G4G-PECL-OPT4G6G	
ISSUED				PRELIMINARY	
SIZE		FSCM NO.		DWG NO.	
A		05XQ0			
SCALE		N:S		SHEET	
				1 OF 1	