

DESCRIPTION

PMI MODEL NUMBER PS-500M2G-10B-SFF-E IS A 0.4 TO 2GHz DIGITALLY CONTROLLED ANALOG PHASE SHIFTER WITH CAPABILITY FOR PHASE SHIFTING FROM 0° TO 360°. THE UNIT CONSISTS OF AN ANALOG PHASE SHIFTER AND A DIGITAL-TO-ANALOG CONVERTER. TEN LOGIC INPUT LINES ALLOW 1024 DISCRETE VALUES OF PHASE.

SPECIFICATIONS


- FREQUENCY RANGE: 0.4 TO 2 GHz
- CONTROL 10 BIT TTL
- INSERTION LOSS 13dB MAX
- PHASE SHIFT 360° TYP
- AMPLITUDE ERROR ±1.0 dB MAX.
- PHASE SHIFT ERROR ±5° MAX.
- SWITCHING SPEED 500 nsec MAX.
- POWER SUPPLY
 - +V: +15V @ 250 mA TYP.
 - V: -15V @ 20 mA TYP.
- SIZE: 4.95" X 3.38" X 1.00"
- WEIGHT: 14 OZ.
- CONNECTORS(RF) SMA FEMALE
- CONNECTOR (CONTROL) 15 PIN SUBMINIATURE D (MALE)
- FINISH BLUE EPOXY POLIMIDE COATING IAW MIL-C-22750,TYPE I OVER EPOXY POLIMIDE PRIMER IAW MIL-P-23377, TYPE I, CLASS 1 OR 3.

ENVIRONMENTAL RATINGS

- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	1/20/15	
	.	.	.	.



ELECTRICAL CONNECTOR PIN ASSIGNMENTS	
PIN LETTER	FUNCTION
1	0.35 DEGREES
2	0.7 DEGREES
3	1.41 DEGREES
4	2.81 DEGREES
5	5.63 DEGREES
6	11.25 DEGREES
7	22.5 DEGREES
8	45 DEGREES
9	90 DEGREES
10	180 DEGREES
11	NC
12	NC
13	+ 15 VDC
14	- 15 VDC
15	GROUND

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE	
DRAWN	BFB	2/3/11		PRODUCT FEATURE	
MODIFIED	JS	1/20/15		PS-500M2G-10B-SFF-E	
ISSUED				0.4-2.0GHz, 0°-360° PHASE SHIFTER	
SCALE N:S		FSCM NO. 05XQ0		DWG NO. PRELIMINARY	
				SHEET 1 OF 1	