

DESCRIPTION

PMI MODEL: PFA-DC2G-10-2W-BNCMF IS A FIXED, ATTENUATOR OPERATING OVER THE DC TO 2.0 GHz FREQUENCY RANGE. THIS MODEL OFFERS 10 ± 0.5 dB OF ATTENUATION WITH AN INPUT POWER OF 2 WATTS MAXIMUM.

SPECIFICATIONS


- FREQUENCY RANGE: ----- DC TO 2.0 GHz
- IMPEDANCE: ----- 50Ω
- ATTENUATION VALUE: ----- 10 dB
- ATTENUATION ACCURACY: ----- ± 0.5 dB
- VSWR: ----- 1.2:1 TYPICAL
- INPUT POWER: ----- 2 WATTS MAXIMUM
- CONNECTORS: ----- BNC (M/F)
- SIZE: ----- (L) 1.80" x $\varnothing 0.59$
(L) 45.72 mm x $\varnothing 14.99$ mm

ENVIRONMENTAL RATINGS

- TEMPERATURE: ----- -20°C TO $+85^{\circ}\text{C}$ (OPERATING)
- HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B
- SHOCK: ----- MIL-STD-202, METHOD 213B COND. B
- VIBRATION: ----- MIL-STD-202, METHOD 204D COND. B
- ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B
- TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY



LABEL

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TEL: (301)-662-5019, FAX: (301)-662-1731

WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com

ISO 9001 CERTIFIED



		TITLE PRODUCT FEATURE PFA-DC2G-10-2W-BNCMF				
APPROVALS	DATE					
DRAWN <i>EMF</i>	<i>11/29/17</i>					
REDRAWN <i>EW</i>	<i>10/15/18</i>	SIZE A	FSCM NO. 05XQ0	DWG NO. PRELIMINARY		REV. -
ISSUED		SCALE N:S			SHEET 1 OF 1	