

DESCRIPTION



PMI MODEL PS-360-2832-5-292FF IS A HIGH SPEED 28.0 TO 32.0 GHZ FREQUENCY RANGE PHASE SHIFTER WITH THE CAPABILITY FOR PHASE SHIFTING FROM 0 TO 349 DEGREES. 10 LOGIC INPUT LINES ALLOW VARIOUS PHASE SHIFT WITH AN LSB OF 0.35 DEGREES.

SPECIFICATIONS

- FREQUENCY RANGE: 28.0 TO 32.0 GHZ
- INSERTION LOSS: 12.0 dB MAX
- VSWR INPUT: 2.0:1
- LSB 0.35°
- CONTROL BITS 10
- SWITCHING SPEED: 500 ns MAX
- POWER SUPPLY: +15 V @ 90 mA MAX
..... -15 V @ 60 mA MAX
- RF CONNECTORS SMA FEMALE INPUT & OUTPUT
- CONTROL TTL THRU "D" MULTIPIN CONNECTOR
- SIZE 1.29" X 1.75" X 0.50"
- FINISH PAINTED BLUE

PIN	FUNCTION
1	+15 VDC
2	GND
3	-15 VDC
4	GND
5	CTL 1 (LSB)
6	CTL 2
7	CTL 3
8	CTL 4
9	CTL 5
10	CTL 6
11	CTL 7
12	CTL 8
13	CTL 9
14	CTL 10 (MSB)
15	NC

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	PRELIMINARY	5/9/17	



ENVIRONMENTAL RATINGS

- TEMPERATURE: -40 °C TO +85°C (OPERATING)
..... -65 °C TO +100 °C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001:2008 CERTIFIED



APPROVALS		DATE		TITLE			
DRAWN	<i>JFK</i>		11/30/10	PRODUCT FEATURE			
REDRAWN	<i>EMF</i>		5/9/17	PS-360-2832-5-292FF-OPT10B			
ISSUED				28 TO 32 GHZ PHASE SHIFTER			
SIZE		FSCM NO.		DWG NO.		REV.	
A		05XQ0		PRELIMINARY		A	
SCALE		N:S		SHEET		1 OF 1	