

DESCRIPTION

PMI MODEL: LM-0518-10-1W-SHS-1-F IS A HIGH SPEED, HIGH POWER HARD DIODE-LIMITER. IT OPERATES OVER THE FREQUENCY RANGE OF 0.5 TO 18GHz

SPECIFICATIONS

- FREQUENCY RANGE: 0.5 TO 18 GHz
- INSERTION LOSS
@-20dBm INPUT: 2.0dB MAX, 1.5dB TYP
- VSWR @-20dBm INPUT: 2.0:1 MAX, 1.5:1 TYP
- LEAKAGE @ 1 WATT
CW INPUT: +14dBm MAX, +10dBm TYP
- SPEED: 10ns
- INPUT POWER: 1 WATT CW, 100 WATTS PEAK,
1us PULSE, 0.1% DUTY CYCLE
DERATED TO 20% AT 125°C
- LIMITING THRESHOLD: +10dBm TYP
- CONNECTORS: SMA (F/M)
- FINISH: PAINTED BLUE
- SIZE: 0.5" X 0.5" X 0.22"


ENVIRONMENTAL RATINGS

- TEMPERATURE: -54°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010
WEIGHT: X.XX oz.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	ORIGINAL RELEASE	4/11/18	



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE		TITLE			
DRAWN	JK	07/31/12		PRODUCT FEATURE			
REDRAWN	SPU	04/11/18		LM-0518-10-1W-SHS-1-SMF			
ISSUED				SIZE	FSCM NO.	DWG NO.	REV.
				A	05XQ0	27034740	A1
SCALE		N:S		SHEET		1 OF 1	