
DESCRIPTION

PMI MODEL; LM-26G40G-14-20W-292FM IS A HIGH POWER LIMITER THAT OPERATES FROM 26,5 GHz TO 40 GHz AND HANDLES 20 WATTS PEAK POWER. THE LEAKAGE POWER IS +14 dBm TYPICAL.

	REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED	
	1	ORIGINAL RELEASE	11/20/15		
	A1	ECN # 16-0194	12/07/16		
	A2	ECN # 17-0223	9/26/17		

SPECIFICATIONS

FREQUENCY RANGE:	26.5 TO 40 GHz
INSERTION LOSS:	4.0 dB MAXIMUM
• PEAK POWER:	20 WATTS (43 dBm)
• PULSE WIDTH:	440 TO 670 ns
• PRF:	600 TO 900 kHz
• DUTY CYCLE:	40%
• LEAKAGE POWER:	+14 dBm TYPICAL
1 dB RECOVERY TIME:	250 ns MAXIMUM
• VSWR:	2.0:1
CONNECTORS:	2.92 mm FEMALE (INPUT) 2.92 mm MALE (OUTPUT)
• SIZE:	0.50" x 0.50" x 0.22"
• WEIGHT:	1.5 oz. TYPICAL
• FINISH:	GOLD PLATED



ENVIRONMENTAL RATINGS

• TEMPERATURE: ------40 °C TO +60 °C (OPERATING) -50 °C TO +70 °C (STORAGE) • HUMIDITY: ----- MIL-STD-202, METHOD 103B COND. B SHOCK: ----- MIL-STD-202, METHOD 213B COND. B VIBRATION; ----- MIL-STD-202, METHOD 204D COND, B • ALTITUDE: ----- MIL-STD-202, METHOD 105C COND. B • TEMPERATURE CYCLE: ----- MIL-STD-202, METHOD 107D COND. A

ALL DIMENSIONS ARE IN INCHES (mm) TOLERANCES: X.XXX

APPROVALS M. Berry

0.50

TEL: (301)-662-5019, FAX: (301)-662-1731 WEB: www.pmi-rf.com, EMAIL: sales@pmi-rf.com ISO 9001 CERTIFIED

> PRODUCT FEATURE LM-26G40G-14-20W-292FM

PLANAR MONOLITHICS INDUSTRIES. INC.

FSCM NO. 05XQ0

7311-F GROVE ROAD

FREDERICK, MARYLAND 21704 USA

TITLE

11/20/15

27028241

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PMI CONFIDENTIAL AND PROPRIETARY

SHEET 1 OF 1 A2