

DESCRIPTION

PLANAR MONOLITHICS INDUSTRIES MODEL LM-30M3G-C3-1-PE2-HERM IS A HIGH POWER LIMITER, SUPPLIED IN OUR STANDARD PE2 HOUSING, THAT WORKS FROM 30MHz TO 3GHz. THIS LIMITER HANDLES 5 WATTS CW WITH A LEAKAGE POWER OF +10 dBm TYP.

SPECIFICATIONS

- FREQUENCY: 30MHz TO 3GHz
- INSERTION LOSS: 1.2 dB (MAX.)
- PEAK POWER: 5 WATTS CW @ +25 C
- LEAKAGE POWER: +10 dBm TYP.
- RECOVERY TIME 1us MAX.
- VSWR: 1.5:1 (MAX.)
- DC BLOCKING: INPUT AND OUTPUT
- CONNECTORS: SMA (IN/OUT)
- WEIGHT: <1 OZ. TYPICAL
- SEALING: HERMETIC

ENVIRONMENTAL RATINGS


- TEMPERATURE: -55°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204B COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A1	INITIAL RELEASE	2/12/19	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE			
DRAWN		2/2/18	PRODUCT FEATURE			
CHECKED		2/22/19	LM-30M3G-C3-1-PE2-HERM			
ISSUED			SIZE	FSCM NO.	DWG NO.	REV.
			A	05XQ0	27036304	A1
			SCALE	N:S		SHEET 1 OF 1