

DESCRIPTION

PMI MODEL NUMBER PVVAN-5010-60-MP IS AN ANALOG CONTROLLED 60dB PIN DIODE ATTENUATOR OPERATING OVER THE FREQUENCY RANGE OF 5.0 TO 10.0 GHz.

SPECIFICATIONS

- FREQUENCY RANGE: 5.0 GHz TO 10.0 GHz
- MEAN ATTENUATION RANGE: 60 dB
- INSERTION LOSS: 2.7 dB MAX
- VSWR: 2.0:1 MAX
- POWER RATING: +20 dBm (OPERATING)
+30 dBm (SURVIVAL)
- ATTENUATION FLATNESS:
 - @ 10dB: ± 0.6 dB
 - @ 20dB: ± 0.9 dB
 - @ 40dB: ± 1.5 dB
 - @ 60dB: ± 1.6 dB
- SWITCHING TIME: 500 ns MAX
- CONTROL: 10 dB/VOLT ANALOG CONTROLLED
- POWER SUPPLY: +12V TO +15V @ 125mA MAX
-12V TO -15V @ 50mA MAX
- POWER/CONTROL CONNECTOR: 15 PIN MICRO-D FEMALE (MATING CONNECTOR SUPPLIED)
- RF CONNECTORS: SMA (F) REMOVABLE
- FINISH: PAINTED BLUE
- SIZE: (L) 2.00" X (W) 1.80" X (H) 0.50"

PIN NO:	J3 PIN FUNCTIONS
1	N/C
2	N/C
3	ANALOG INPUT
4	GND
5	N/C
6	N/C
7	N/C
8	N/C
9	N/C
10	N/C
11	N/C
12	N/C
13	+12 or +15 VDC
14	N/C
15	N/C

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ± 0.020
X.XXX ± 0.010


ENVIRONMENTAL RATINGS

- TEMPERATURE: -55°C TO + 85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	-	PRELIMINARY	11/14/17

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



APPROVALS		DATE	TITLE PRODUCT FEATURE PWAN-5010-60-MP				REV.
DRAWN <i>KM</i>	11/9/11						
REDRAWN <i>BW</i>	11/14/17						
ISSUED			SIZE A	FSCM NO. 05XQ0	DWG NO. PRELIMINARY	REV. —	
			SCALE N:S			SHEET	1 OF 1